

# Installation on Debian-Based Systems

*Qosium Probe can be installed by using Debian package management system. This works on Debian, Ubuntu, Raspbian (Raspberry Pi), and other Debian-based Linux distributions. Installation can be done in terminal or by using package manager applications like the Software Center and Synaptic.*

# Table of Contents

- 1. Preparations ..... 3
- 2. Package Pre-checks (Optional) ..... 3
- 3. Installation ..... 3
- 4. Uninstallation ..... 3

## 1. Preparations

First, [sign in](#) to your account and access [your downloads page](#). Then download Qosium Probe for the target machine. The package is typically named as `QosiumProbe_<version_details>.deb`, where the `<version_details>` part depends on version to another and may contain many identifiers.

## 2. Package Pre-checks (Optional)

The Debian package can be verified by opening Terminal and running:

```
dpkg --info QosiumProbe_<version_details>.deb
```

To see what will be installed and where to, run:

```
dpkg --contents QosiumProbe_<version_details>.deb
```

## 3. Installation

To install a fresh or upgrade an existing Qosium Probe in a machine, open Terminal and run:

```
sudo dpkg -i QosiumProbe_<version_details>.deb
```

It is also possible to use *apt* for installation. This method installs automatically all dependencies. Installation using *apt-get* happens the following way:

```
sudo apt-get install ./QosiumProbe_<version_details>.deb
```

The installation process asks all the relevant details, e.g., whether or not to install Qosium Probe as a Systemd service, etc.

After installation, you can check which version of Qosium Probe is installed by running:

```
dpkg -l qosiumprobe
```

## 4. Uninstallation

To remove Qosium Probe from the device, run:

```
sudo dpkg -r qosiumprobe
```